


Geberit Mapress Copper coupling



Example image

Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)

- For technical building systems, industry and shipbuilding

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54$ mm
- Seal ring made of CIIR, black, up to $\varnothing \leq 54$ mm
- Seal ring made of EPDM, black, from $\varnothing > 54$ mm
- Pressing socket with transparent protection plug

Technical data

Material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, \varnothing	L	Z
62001	10	12 mm	4.2 cm	0.8 cm
62002	12	15 mm	4.8 cm	0.8 cm
62003	15	18 mm	4.8 cm	0.8 cm
62004	20	22 mm	5 cm	0.8 cm
62005	25	28 mm	5.4 cm	0.8 cm
62006	32	35 mm	6.2 cm	1 cm
62007	40	42 mm	7.1 cm	1.1 cm
62008	50	54 mm	8.3 cm	1.3 cm
62013	100	108 mm	17.6 cm	2.6 cm
62010	65	66.7 mm	12.7 cm	2.7 cm
62011	65	76.1 mm	12.7 cm	2.1 cm
62012	80	88.9 mm	14.5 cm	2.5 cm