


Geberit Mapress Copper bend



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)

- For technical building systems, industry and shipbuilding

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54$ mm
- Seal ring made of CIIR, black, up to $\varnothing \leq 54$ mm
- Seal ring made of EPDM, black, from $\varnothing > 54$ mm
- Pressing socket with transparent protection plug

Technical data

Material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, \varnothing	arc	L	Z
60601	10	12 mm	45 °	2.6 cm	0.9 cm
60101	10	12 mm	90 °	3.1 cm	1.4 cm
60602	12	15 mm	45 °	3.6 cm	1.6 cm
60102	12	15 mm	90 °	3.8 cm	1.8 cm
60603	15	18 mm	45 °	2.9 cm	0.9 cm
60103	15	18 mm	90 °	4.2 cm	2.2 cm
60604	20	22 mm	45 °	3.2 cm	1.1 cm
60104	20	22 mm	90 °	4.7 cm	2.6 cm
60605	25	28 mm	45 °	3.7 cm	1.4 cm
60105	25	28 mm	90 °	5.7 cm	3.4 cm
60606	32	35 mm	45 °	4 cm	1.4 cm
60106	32	35 mm	90 °	6.5 cm	3.9 cm
60607	40	42 mm	45 °	4.7 cm	1.7 cm
60107	40	42 mm	90 °	7.6 cm	4.6 cm
60608	50	54 mm	45 °	5.7 cm	2.2 cm
60108	50	54 mm	90 °	9.5 cm	6 cm
60613	100	108 mm	45 °	14.3 cm	6.8 cm
60113	100	108 mm	90 °	23 cm	15.5 cm
60610	65	66.7 mm	45 °	9.2 cm	4.2 cm
60611	65	76.1 mm	45 °	10.3 cm	5 cm
60612	80	88.9 mm	45 °	11.7 cm	5.7 cm
60110	65	66.7 mm	90 °	14.1 cm	9.1 cm
60111	65	76.1 mm	90 °	15.9 cm	10.6 cm
60112	80	88.9 mm	90 °	18.5 cm	12.5 cm



-
- In 2020, the dimensions of bend d15/45° will be modified. The new dimensions are listed in the overview "Dimensional changes for Geberit Mapress Copper 2020".