


Geberit Mapress Copper T-piece, equal



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)

- For technical building systems, industry and shipbuilding

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of CIIR, black, up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of EPDM, black, from $\varnothing > 54\text{ mm}$
- Pressing socket with transparent protection plug

Technical data

Material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, \varnothing	L	L1	l	Z	Z1
61000	10	12 mm	6.2 cm	3.1 cm	3.1 cm	1.4 cm	1.4 cm
61002	12	15 mm	6.4 cm	3.1 cm	3.2 cm	1.2 cm	1.2 cm
61003	15	18 mm	6.8 cm	3.4 cm	3.4 cm	1.4 cm	1.4 cm
61004	20	22 mm	7.4 cm	3.7 cm	3.7 cm	1.6 cm	1.6 cm
61005	25	28 mm	8.4 cm	4.2 cm	4.2 cm	1.9 cm	1.9 cm
61006	32	35 mm	10 cm	5.9 cm	5 cm	2.4 cm	3.3 cm
61007	40	42 mm	11.4 cm	6.6 cm	5.7 cm	2.7 cm	3.6 cm
61008	50	54 mm	13.8 cm	7.8 cm	6.9 cm	3.4 cm	4.3 cm
61013	100	108 mm	31 cm	15.3 cm	15.5 cm	8 cm	7.8 cm
61010	65	66.7 mm	22 cm	10.5 cm	11 cm	6 cm	5.5 cm
61011	65	76.1 mm	23 cm	11.0 cm	11.5 cm	6.2 cm	5.7 cm
61012	80	88.9 mm	26 cm	12.7 cm	13 cm	7 cm	6.7 cm